751 Old Brandy Road
Culpeper, Virginia 22701

Tele: 540 825-2111
Fax: 540 825-2238

DATALINE®

Description

	mm	Inch
CONDUCTOR #18 AWG, 7/0.0152" (0.39 mm) Nickel-Coated Copper	1.17	0.046
INSULATION - Dual Pass 0.0305" (0.76 mm) Wall PFA/ETFE	2.72	0.107
ARMOR: UNS N08926 (31Mo Alloy)		
Inner: 12/0.031" (0.79 mm)	4.09	0.161
Outer: 18/0.031" (0.79mm)	5.66	0.223



CABLE CHARACTERISTICS
(Nominal Values @ 20℃)

	Metric	English
PHYSICAL		
Overall Dimensions	5.66 mm	0.223 in
Weight in Air	143 kg/km	96 lb/kft
Weight in Freshwater	123 kg/km	82 lb/kft
Temperature Rating, normal	246℃	475℉
intermittent	260℃	500℉
armor in corrosive environment	149℃	300℉
MECHANICAL		
Breaking Strength	21.3 kN	4,800 lbf
Bend Diameter	30 cm	12 in
Elongation (approximate)	0.58 m/km/kN	2.6 ft/kft/klbf
ELECTRICAL		
Voltage Rating	1,200 Vdc	1,200 Vdc
Insulation Resistance @ 500 Vdc	15,000 MΩ•km	50,000 MΩ•kft
dc Resistance		
cdr	25.3 Ω/km	7.7 Ω/kft
armor	70.0 Ω/km	21.3 Ω/kft
Capacitance (cdr - armor)	148 pF/m	45 pF/ft
Velocity of Propagation @ 1 MHz	65%	65%

PROPRIETARY; Use Pursuant to Company Instructions

Tyco Electronics *The Rochester Corporation*

Rochester Stock Type 1-H-226K
(with UNS N08926 Armor)

Date	Page	Revision	Part No.
08/04/2009	1	T	A216229